


# QC VOC 100 WB



## Material Safety Data Sheet

QC Construction Products  
11901 Gavin Rd  
Laredo, TX 78045

### NFPA Rating



### HMIS Rating

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

### EMERGENCY PHONE:

CHEMTREC: 800.424.9300 (nights/weekends)

**Notice:** The following information is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

## I. IDENTIFICATION:

Product Name: QC VOC 100 WB  
Synonymous: N/A  
Chemical Family: N/A  
Chemical Formula: Proprietary  
D.O.T. Hazard Class: Paint (Non-Hazardous)  
Appearance & Odor: Clear liquid, sweet odor.

## II. HAZARDOUS COMPONENTS & EXPOSURE LIMITS:

<i>Composition</i>	<i>%</i>	<i>ACGIH TLV-TWA</i>	<i>CAS NO.</i>
Water	74-84%	Not established	7732-18-5
Ammonia salt of modified styrene acrylic polymers	15-25%	Not established	Proprietary
Dipropylene glycol n-butyl ether	1-2%	Not established	299-11-28-2

## III. TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Specific Gravity (H<sub>2</sub>O=1): 0.834  
Boiling Point: Unknown  
Melting Point: N/A  
Vapor Pressure: 400 @ 104 °F (40 °C)  
Vapor Density: Unknown  
Evaporation Rate: 7.7 (Butyl Acetate=1)  
Solubility In Water: Miscible

## IV. FIRE EXPLOSION & REACTIVITY DATA:

Flash Point: None  
Flammable Limits: Not available  
Firefighting Media: Foam, water fog, carbon dioxide or dry chemical.

Firefighting Procedure:	Wear self-contained breathing apparatus.
Special Firefighting Procedure:	Warning. Flammable! Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear (helmet with face-shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.
Unusual Fire Hazards:	Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup, which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.
Reactivity:	Stable
Incompatibilities:	N/A
Decomposition or Byproducts: Hazardous Polymerization:	Fire Conditions: Carbon monoxide, hydrochloric acid, hydrofluoric acid and phosgene. Will not occur.
Conditions to Avoid:	Heat, sparks and open flames.

## V. HEALTH HAZARD DATA

Inhalation:	Irritation to nose, throat and respiratory tract. High vapor concentrations may cause central nervous system depression or narcosis.
Skin Contact:	Irritant. Excessive skin contact can cause drying and irritation.
Eye Contact:	Irritant.
Ingestion:	Do not induce vomiting. Aspiration of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.
Signs and Symptoms:	Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness and nausea; in extreme cases, unconsciousness and death may occur. Coughing, labored breathing and cyanosis (bluish skin) may evidence aspiration pneumonitis; in severe cases, death may occur.
Aggravated Medical Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

### ***Emergency and First Aid Procedures***

Inhalation:	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get immediate medical attention.
Skin Contact:	Remove contaminated clothing and shoes. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.
Eye Contact:	Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.
Ingestion:	Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

## VI. SPILL PROCEDURES & WASTE DISPOSAL

Spill: Caution: Combustible. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Contain spill and absorb. Keep product from entering storm drains.

Waste  
Disposal: Dispose of in accordance with Federal, State and Local regulations.

Precautions for  
Safe Handling  
And Storage: Keep liquid and vapor away from heat, sparks and flame. Surfaces that are sufficiently hot may ignite even liquid product in the absence of sparks and flame.

Other  
Precautions: Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash-fire can result. Keep containers closed when not in use. Use adequate ventilation. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operation on or near containers. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.  
This is a commercial product, not intended for home use. Keep out of reach of children.

## VII. PROTECTIVE CONTROL MEASURES

Respirator: NIOSH-approved respirator for organic vapors (when TLV exceeded)

Ventilation: Yes  
Local Exhaust: Yes  
Mechanical: In enclosed areas

Special: N/A

Protective Gloves: Yes

Eye Protection: Yes

Other Protective  
Clothing Required: Normal for paint and solvent seal application.

Work/Hygiene  
Practices: Wash hands after use and before eating, drinking or smoking.